



Description: Head Light  
Part Number: 111059 - 111085 - 111194 - 111193  
Application: 1997-2004 Dodge Dakota / 1998-2003 Dodge Durango



Tools needed: 12mm socket,  
phillips screwdriver, wire splicer,  
electrical tape.



Pull out the head light rubber  
guard.



Locate the phillips screw  
between the headlight and turn  
signal and remove it.



Pull out the turn signal and  
corner from the vehicle.



Once you get it off twist off the  
light bulb sockets from the light.



Locate the three 12mm screws  
holding in the headlight and  
remove them.



Unplug the headlight wire  
harness.



Pull out the new Anzo headlight  
from the box.



On the new headlight locate the  
two loose wires. Red(+) positive  
black (-) negative.



On the new headlight locate the  
194 light bulb harness.



Splice the red(+) wire to the tan  
and black (-) to the black wire to  
power up the halos.



On the original wire harness on  
the vehicle remove the 194 bulb  
from the wire harness.



Next remove the 3157 bulb from  
the original wire harness of the  
vehicle.



Now unplug the 3157 light bulb  
socket from the harness.



On the new Anzo headlight plug in the 194 bulb in to the original wire harness of the vehicle



Now plug in the light bulb wire harness into the new Anzo supplied light bulb socket.



Locate the 3157 wedge connector from our light and plug into the wire harness make sure the black wire lines up with the black wire from the light bulb wire harness.



Now connect the head light wire harness.



Test all functions making sure everything works properly before driving.

### Note

The following adjustment procedure should only be don't if you have excessive gaps between the fender and the light housing.



On the back side of the light there are 3 adjustment screws. You can turn these screws to move the bracket closer to the housing. by doing this you will be able to adjust the gap between the fenders and the light. You may have to take the light out a couple times and adjust the screws to get the desired gap.

AnzoUSA™ products are covered, by a limited one (1) year warranty, to be free of manufacturer's defects. However, certain AnzoUSA™ product categories have warranty policies which differ from this standard, please contact your representative for detailed category information. Damage due to improper installation or road hazards is not covered. Seller and manufacturers' only obligations shall be to replace the product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.